



Custom Heat Seal Labels - Small Orders • 5-7 Day Turnaround

A Permanent label designed for Industrial Water Wash and Dry Cleaning
Applied label — 7 mil thickness • Smooth • Supple • Symmetrical •
 Used on Natural, Synthetics, Knit Fabric, Woven Fabric.

Heat Seal Label C-Perf.



1.3"w x .38"h
L-2010



1.5"w x .75"h
L-2025



Material: White Polyester
Adhesive: Heat Seal Adhesive

Stock Size: 1.3w" x .38"h (7 mil thick)
 1.5w" x .75"h (7 mil thick)
 C-Perf. Labels are supplied in rolls of sequentially numbered labels, perforated, and ready to Heat Seal to your garments or fabric.

Custom Options: Any barcode/digits/text can be printed on these custom-ordered labels.
 (Standard is 8-digit, code interleaved 2 of 5)

Pricing:	\$0.23/label	300– 2,000 labels
	Set-up Fee/Per Run	\$20.00
	Copy change fee	\$10.00

Heat Seal Application Specifications:
 Temperature: 380-400F degrees
 Time: 7-10 seconds, depending on fabric thickness
 Pressure: 25-28 lbs. of inter-platen pressure/platen square inch

Exceeds Industrial Wash Test and Dry Cleaning Parameters
 125X commercial wash cycles, commercial washer 160 degrees
 60X commercial dry-cleaning in solvent Perchloroethylene
 (Dry Cleaning & Laundry Institute International)

For ordering labels, prices, or more information contact Amber@ipc-tags.com
 Customer Service: 817-714-8400 • Order Fax: (817) 887-1725 • Corporate (972) 822-0934