

Quality Heat Seal Labels for Textile Applications

Un-Cut No Perf, Heat Seal Material

Quick Seal Blank Rolls

**Printable Heat Seal Rolls for
Uniforms • Linens • Textiles •
Clothing • Formal Wear •
Costumes • Draperies**



Material: White Polyester

Adhesive: Heat Seal Adhesive

Description: **Smooth • Supple**

Permanent in Water Wash. 7-8 mil thickness

Designed for printing with Thermal Ink Ribbon or UV Printing.

Rolls are ready for print, cut, and heat seal.

Each roll of 100 yards includes one 110 yard roll-thermal transfer resin ribbon.

Rolls-3" diameter core. Ribbon-1" diameter core.

Removable with re-application of heat @375-380F.

Widths: 1.5" X 100 yards (L-411015) 8cm w X 100 yards (L-41108CMY)
Other widths available. Call or email for pricing and quantity pricing.

Heat Seal Application Specifications:

Temperature: 375-385F degrees

Time: 4-5 seconds, depending on fabric thickness

Pressure: 25-28 lbs. of inter-platen pressure/platen square inch

Removable with re-application of heat @375-380F.

Exceeds Industrial Wash Test

100X commercial wash cycles, AATCC TM96 IVc.

HT/HS Codes: Heat Seal Material (3919100000) Ribbon (9612.10.9030)

Meets AAFA and OEKE Tex 100 Standards

For samples or ordering labels, prices, or more information contact Amber@ipc-tags.com
Customer Service: 817-714-8400 • Order Fax: (817) 887-1725 • Corporate (972) 822-0934