



Custom Heat Seal Labels - Small Orders • 5-7 Day Turnaround

A Permanent label designed for Industrial Water Wash and Dry Cleaning

Applied label — 7 mil thickness • Smooth • Supple • Symmetrical •

Used on Natural, Synthetics, Knit Fabric, Woven Fabric.

Heat Seal Label C-Perf.



1.3"w x .38"h
L-2010



1.5"w x .75"h
L-2025



Material: White Polyester
Adhesive: Heat Seal Adhesive

Stock Size: 1.3w" x .38"h (7 mil thick)
1.5w" x .75"h (7 mil thick)
C-Perf. Labels are supplied in rolls of sequentially numbered labels, perforated, and ready to Heat Seal to your garments or fabric.

Custom Options: Any barcode/digits/text can be printed on these custom-ordered labels.
(Standard is 8-digit, code interleaved 2 of 5)

Pricing: \$0.23/label 300- 2,000 labels
Set-up Fee/Per Run \$20.00
Copy change fee \$10.00

Heat Seal Application Specifications:

Temperature: 380-400F degrees
Time: 7-10 seconds, depending on fabric thickness
Pressure: 25-28 lbs. of inter-platen pressure/platen square inch

Exceeds Industrial Wash Test and Dry Cleaning Parameters

125X commercial wash cycles, commercial washer 160 degrees

60X commercial dry-cleaning in solvent Perchloroethylene
(Dry Cleaning & Laundry Institute International)

IPC-Tags warrants successful laboratory testing of labels for wash and dry cleaning of garments. However, no test can duplicate each customer's processes so IPC-Tags makes no other warranty. On request, we will provide test labels free of charge for customer testing of label suitability in their environment.

For ordering labels, prices, or more information contact Amber@ipc-tags.com
Customer Service: 817-714-8400 • Order Fax: (817) 887-1725 • Corporate (972) 822-0934