



**'HT' - Heat Transfer - A Permanent Barcode Label
for Industrial Water Wash and Dry Cleaning Environments**

**Laser-Printed • Lint-Free • Anti-Static
Applied label — 2-3 mil thickness • Smooth & Professional Appearance**

**Proven Performance FOR OVER 30 YEARS on
Uniforms • Linens • Formal Wear Attire • Costumes • CleanRoom Apparel • Tech Fabrics
Natural Fibers • Synthetics • Knit Fabric • Woven Fabric
Our Label Remains Scannable and Readable for the Life of the Garment**

**Label Description &
Dimensions**

**In-Stock and Available for
Shipment Today**

99 Label

8-digit

*10 mm x 33 mm or
3/8" x 1-5/16"*



72 Label

8 or 10 digit

*19 mm x 39 mm or
3/4" x 1-1/2"*



84 Label

12-digit

*13 mm x 60 mm or
1/2" x 2-3/8"*



60 Label

12-digit

*19 mm x 60 mm or
3/4" x 2-3/8"*



Heat Seal Machine Application Specifications:

Temperature: 380-400 degrees

Time: 7-12 seconds

Pressure: 25-28 lbs. of inter-platen pressure per
platen square inch

For ordering in-stock labels, prices, or more information contact Amber@ipc-tags.com
Customer Service: 817-714-8400 • Order Fax: (817) 887-1725 • Corporate (972) 822-0934